

Line-PRO 1000 Series

Striping & Marking Paint

International Coatings introduces its **Line-PRO 1000 Traffic and Parking Lot Paint**. Durable, long-lasting and ideal for either concrete or asphalt surfaces, Line-PRO 1000 is the right product for all of your marking and striping needs. Whether striping highways, streets, parking lots, sidewalks, or driveways, Line-PRO 1000 can be easily applied using conventional or airless spray equipment.

Line-PRO 1000 has been formulated with carefully selected raw materials that have been proven to withstand harsh weather, and heavy traffic and road conditions.

PRODUCT FEATURES:

- ➔ **Line-PRO 1000** is a water-base acrylic paint that is ready to use and easy to apply.
- ➔ **Line-PRO 1000** is non-flammable and cleans up with water.
- ➔ **Line-PRO 1000** is available in white, yellow (non-leaded), black, blue, green and red.
- ➔ **Line-PRO 1000** is durable and performs equally well on concrete or bituminous (asphalt) surfaces.
- ➔ **Line-PRO 1000** can be used for roadway, parking lot striping, and airport runway and tarmac marking or legends.
- ➔ **Line-PRO 1000** can be applied using conventional or airless spray equipment.
- ➔ **Line-PRO 1000** meets SCAQMD Rule 1113 requirements.

Line-PRO 1000 is available from International Coatings' exclusive network of distributor companies. Order **Line-PRO 1000** today. Contact us at (800) 423-4103 (within the U.S. only) or (562) 926-1010, or visit www.LineProTraffic.com for more information.

International Coatings is a leading manufacturer of industrial coatings, adhesives, textile screen-printing inks and specialty plastic compounds. International Coatings has over 45 years of combined experience in traffic paint and coatings!



International Coatings, 13929 E. 166th St., Cerritos, CA 90703
Toll-Free U.S. (800) 423-4103 or (562) 926-1010 • Fax (562) 926-9486
www.LineProTraffic.com • www.iccink.com • icinfo@iccink.com

International Coatings™
Line-PRO™ Traffic Markings

Line-PRO 1000 Series Technical Data Sheet

PRODUCT DESCRIPTION: Water-base, acrylic striping and marking paint, specifically formulated for ease of use and durability.

COLORS: TP 1102 White
TP 1202 Yellow (non-leaded)
TP 1302 Black
TP 1401 Red
TP 1502 Blue
TP 1601 Green

PRODUCT SPECIFICATIONS: Meets SCAQMD Rule 1113 requirements.

PRODUCT USAGE: Recommended for striping and/or marking of roads, airport runways and tarmacs, driveways, parking lots, etc. Can be applied to a variety of substrates, including asphalt and concrete.

COVERAGE: Approximately 310 - 325 feet of 4" stripe at 16 mils.

APPLICATION: Can be applied using conventional or airless spray equipment. Apply only when paint and surface temperatures are at least 50° F and rising. Avoid application when relative air humidity is above 80%. Paint should be applied only on clean, dry surfaces.

DRYING TIMES: Dries to no pickup in 10 minutes at 16 mils when surface temperatures are above 50° F.

PACKAGING: Available in 5-gallon pails and 55-gallon drums.

SURFACE PREP: Ensure that surface is free of dirt and grease. Be sure to remove any loose or peeling paint. For best performance, new concrete or asphalt should be allowed to cure for at least 30 - 60 days prior to applying paint to avoid bleeding and loss of adhesion to the substrate. New concrete surfaces should be free of any curing compounds that may affect the adhesion of any traffic or curb paints. Protect any newly painted areas until thoroughly dry.

STORAGE: Keep product away from high heat and keep product from freezing. Stirring paint prior to use is recommended to ensure uniform consistency and quality. Seal containers tightly after use to avoid spillage, or evaporation and skinning.

SAFETY: Consult MSDS sheet or product label for additional information on safety and first aid procedures.

TECHNICAL DATA

Physical Properties:		White	Other Colors
Density (#/gal, min):		12.0 ± 0.5	11.6 ± 0.5
Volatile Organic Compounds (gm/ltr) max.:		100	100
Viscosity @ 25°C ± 1°C (KU):	ASTM D562	80 - 90	80 - 90
% Solids by Weight, minimum:		60	60
Dry To No Pick-Up (Minutes):	ASTM D711	15 - 30	15 - 30
Fineness of Dispersion (Hegman):	ASTM D1210	3	3

Distributed By:


International
Coatings™
Line-PRO™ Traffic Markings