

# Line-PRO 2000 Series

## Federal Specification TTP-1952 E

International Coatings' Line-PRO 2000 Series Traffic and Parking Lot Paint meets Federal Specification TTP-1952E. Durable, long-lasting and formulated specifically for asphaltic or portland cement, Line-PRO 2000 is the right product for all of your marking needs. Whether striping highways, airport runways, parking lots, sidewalks, or driveways, Line-PRO 2000 can be applied to a variety of surfaces easily.

Line-PRO 2000 has been formulated with carefully selected raw materials that have been proven to withstand harsh weather, and heavy traffic and road conditions.

### PRODUCT CHARACTERISTICS:

- ➡ **Line-PRO 2000** is waterborne, 100% acrylic based traffic paint that is ready to use with no thinning required.
- ➡ **Line-PRO 2000** is available in white, yellow (non-leaded), and black.
- ➡ **Line-PRO 2000** will perform equally well on concrete or asphalt surfaces and can be used for roadway, airport tarmac and runway, or parking lot striping, marking or legends.
- ➡ **Line-PRO 2000** is durable and demonstrates excellent bead retention.
- ➡ **Line-PRO 2000** can be applied using conventional or airless spray equipment.
- ➡ **Line-PRO 2000** meets Federal Specification TTP-1952 E requirements.

**Line-PRO 2000** is available from International Coatings' exclusive network of distributor companies. Order **Line-PRO 2000** today. Contact us at (800) 423-4103 (within the U.S. only) or (562) 926-1010, or visit [www.LineProTraffic.com](http://www.LineProTraffic.com) for more information.

International Coatings is a leading manufacturer of industrial coatings, adhesives, textile screen-printing inks and specialty plastic compounds. International Coatings has over 45 years of combined experience in traffic paint and coatings!



International Coatings, 13929 E. 166th St., Cerritos, CA 90703  
Toll-Free U.S. (800) 423-4103 or (562) 926-1010 • Fax (562) 926-9486  
[www.LineProTraffic.com](http://www.LineProTraffic.com) • [www.iccink.com](http://www.iccink.com) • [icinfo@iccink.com](mailto:icinfo@iccink.com)

**International Coatings™**  
Line-PRO™ Traffic Markings

# Line-PRO 2000 Technical Data Sheet

**PRODUCT DESCRIPTION:** Water-base, 100% acrylic traffic and parking lot marking paint, specifically formulated for ease of use and durability.

**COLORS:** 2101 White  
2201 Yellow (non-leaded)  
2301 Black

**PRODUCT SPECIFICATIONS:** Meets Federal Specification TTP-1952 E requirements.

**PRODUCT USAGE:** Recommended for striping or marking roads, airport runways and tarmacs, driveways, parking lots, etc. Can be applied to a variety of substrates including asphalt and concrete.

**COVERAGE:** Approximately 310 - 325 feet of 4" stripe at 16 mils.

**APPLICATION:** Can be applied using conventional or airless spray equipment. Apply only when paint and surface temperatures are at least 50° F and rising. Avoid application when relative air humidity is above 80%. Paint should be applied only on a clean, dry surface.

**DRYING TIMES:** Dries to no pickup in 10 minutes at 16 mils when surface temperatures are above 50° F.

**PACKAGING:** Available in 5-gallon pails and 55-gallon drums and 250-gallon totes.

**SURFACE PREP:** Ensure that surface is free of dirt and grease. Be sure to remove any loose or peeling paint. For best performance, new concrete or asphalt should be allowed to cure for at least 30 - 60 days prior to applying paint to avoid bleeding and loss of adhesion to the substrate. New concrete surfaces should be free of any curing compounds that may affect the adhesion of any traffic or curb paints. Protect any newly painted areas until thoroughly dry.

**STORAGE:** Keep product away from high heat and keep product from freezing. Stirring paint prior to use is recommended to ensure uniform consistency and quality. Seal containers tightly after use to avoid spillage or evaporation and skinning.

**SAFETY:** Consult MSDS sheet or product label for additional information on safety and first aid procedures.

## TECHNICAL DATA:

| Physical Properties                       |                | Min             | Max |
|---|----------------|-----------------|-----|
| Density (#/gal):                          |                | 13.74 ± 0.2     |     |
| Volatile Organic Compounds (gm/ltr) max.: |                | ---             | 100 |
| Viscosity @ 25°C ± 1°C (Ku):              |                | 80              | 90  |
| % Solids by Volume:                       | Yellow & White | 60              |     |
|   | Other Colors   | ASTM D697 58    |     |
| Pigment, Percent By Weight (± 2%):        |                | ASTM D3723 60   | 62  |
| Dry Opacity:                              | White & Colors | ASTM D2805 0.92 |     |
|   | Black          | 1.0             |     |
| Dry To No Pick-Up (Minutes):              |                | ASTM D711 ---   | 10  |
| Directional Reflectance (%min.):          | White          | ASTM E1347 85   |     |
| Fineness of Dispersion (Hegman):          |                | ASTM D1210 3    |     |

Line-PRO 2000 can be custom-formulated to meet particular state, county and city specifications

Distributed By:

  
International  
Coatings™  
Line-PRO™ Traffic Markings