

Line-PRO 4000 Traffic Paint

Federal Specification TTP-115F, Low VOC

International Coatings introduces its **Line-PRO 4000 Low VOC, Traffic and Parking Lot Paint**. Durable, long-lasting and ideal for either concrete or asphalt surfaces, Line-PRO 4000 is the right product for all of your marking needs. Whether striping highways, streets, parking lots, sidewalks, or driveways, Line-PRO 4000 is fast-drying and easy to apply.

Line-PRO 4000 has been formulated with carefully selected raw materials that have been proven to withstand harsh weather, and heavy traffic and road conditions.

PRODUCT FEATURES:

- ➡ **Line-PRO 4000** is a modified acrylic, one-component, low VOC, solvent-base traffic paint that is ready to use and easy to apply.
- ➡ **Line-PRO 4000** is available in white, yellow (non-leaded), black, red and Handicap blue. In addition, we also feature a Thinner as well as a Clear Thermoplastic Primer.
- ➡ **Line-PRO 4000** will perform equally well on concrete or asphalt surfaces, and can be used for roadway, airport tarmac and runway, or parking lot striping, marking or legends.
- ➡ **Line-PRO 4000** is fast drying, even at low temperatures. It is durable and long-lasting.
- ➡ **Line-PRO 4000** has excellent bead retention.
- ➡ **Line-PRO 4000** can be applied using conventional or airless spray equipment.
- ➡ **Line-PRO 4000** meets CALTRANS PT-150VOC (A) specification, Federal Specification TTP-115F and SCAQMD Rule 1113.

Line-PRO 4000 is available from International Coatings' exclusive network of distributor companies. Order **Line-PRO 4000** today. Contact us at (800) 423-4103 (within the U.S. only) or (562) 926-1010, or visit www.LineProTraffic.com for more information.

International Coatings is a leading manufacturer of industrial coatings, adhesives, textile screen-printing inks and specialty plastic compounds. International Coatings has over 45 years of combined experience in traffic paint and coatings!



International Coatings, 13929 E. 166th St., Cerritos, CA 90703
Toll-Free U.S. (800) 423-4103 or (562) 926-1010 • Fax (562) 926-9486
www.ProLineTraffic.com • www.iccink.com • icinfo@iccink.com

International Coatings™
Line-PRO™ Traffic Markings

Line-PRO 4000 Technical Data Sheet

PRODUCT DESCRIPTION: Solvent-base, low VOC, modified acrylic traffic and parking lot marking paint, specifically formulated for ease of use and durability.

COLORS: TP 4000 Solvent
TP 4101 White
TP 4201 Yellow (non-leaded)
TP 4301 Black
TP 4401 Red
TP 4501 Handicap Blue
TP 4500 Clear Thermoplastic Primer

PRODUCT SPECIFICATIONS: Meets CALTRANS PT-150VOC (A) specification, Federal Specification TTP-115F and SCAQMD Rule 1113.

PRODUCT USAGE: Recommended for striping and/or markings on roads, airport tarmacs and runways, driveways, parking lots, curbs, etc. Can be applied to a variety of substrates, including asphalt and concrete.

COVERAGE: Approximately 310 - 325 feet of 4" stripe at 16 mils.

APPLICATION: Can be applied using conventional or airless spray equipment. Apply only when paint and surface temperatures are at least 40° F and rising. Avoid application when relative air humidity is above 80%. Lower temperatures may also affect drying time. Paint should be applied only on a clean, dry surface.

DRYING TIMES: Dries to no pickup in 5 - 10 minutes at 16 mils when surface temperatures are above 50° F.

PACKAGING: Available in 5-gallon pails and 55-gallon drums.

SURFACE PREP: Ensure that surface is free of dirt and grease. Be sure to remove any loose or peeling paint. For best performance, new concrete or asphalt should be allowed to cure for at least 30 - 60 days prior to applying paint to avoid bleeding and loss of adhesion to the substrate. New concrete surfaces should be free of any curing compounds that may affect the adhesion of any traffic or curb paints. Protect any newly painted areas until thoroughly dry.

STORAGE: Keep product away from high heat. Stirring paint prior to use is recommended to ensure uniform consistency and quality. Seal containers tightly after use to avoid spillage or evaporation and skinning.

SAFETY: Consult MSDS sheet or product label for additional information on safety and first aid procedures. Keep paint away from smoke or flames as solvents are flammable.

TECHNICAL DATA

Physical Properties:		White	Other Colors
Density (#/gal) ±0.10:	ASTM D1475	11.79	11.38
Volatile Organic Compounds (gm/ltr) max.:		100	100
Viscosity @ 25°C ± 1°C (Ku):	ASTM D562	70 - 88	70 - 88
Pigment, Percent By Weight (± 2%):	ASTM D2698	54.6	53.3
Dry To No Pick-Up (Minutes):	ASTM D711	10 max	10 max
NVV By Weight of Vehicle (% min.):	ASTM D2369	37	37
Fineness of Dispersion (Hegman):	ASTM D1210	3	3
% Solids by Weight (min. ±1.0%):	ASTM D2369	72.2	71.5

Distributed By:

International Coatings™
Line-PRO™ Traffic Markings